

AMENDMENTS TO THE CLAIMS:

- 92
1. (Currently amended) A liquid crystal display panel, comprising:
an array substrate on which a driving element for controlling a driving voltage and a display electrode to which a voltage is applied through the driving element are formed;
a first polarization layer for polarizing the light passing through the array substrate;
a liquid crystal layer including ~~having~~ a liquid crystal material;
a color filter substrate on which a color filter comprising ~~made of~~ a color-material film is formed; and
a second polarization layer for polarizing the light passing through the color filter substrate,
wherein the array substrate, the first polarization layer, the liquid crystal layer, the color filter substrate, and the second polarization layer are successively superposed.
 2. (Original) The liquid crystal display panel according to Claim 1, wherein a common electrode is formed on the array substrate and an electric field is generated in a direction parallel with the array substrate by applying a voltage between the display electrode and the common electrode.
 3. (Withdrawn and Currently Amended) The liquid crystal display panel according to Claim 1, wherein a common electrode is formed on the color filter substrate and an electric field is generated in a ~~the~~ direction vertical to the array substrate by applying a voltage between the display electrode and the common electrode.

4. (Original) A liquid crystal display device, comprising:

Q2 cont. a liquid crystal display panel in which an array substrate and a color filter substrate are arranged to sandwich a liquid crystal layer; and

a backlight unit for applying light to the liquid crystal display panel from the outside of the array substrate,

wherein the light reflected from the array substrate of the liquid crystal display panel directly returns to the backlight unit without passing through other layers.

5. (Currently amended) The liquid crystal display device according to Claim 4, wherein:

a polarization layer is disposed set between the array substrate and the color filter substrate of the liquid crystal display panel; and

the light reflected from the array substrate returns to the backlight unit without passing through the polarization layer so as to improve the light-recycling efficiency of the backlight unit.

6. (Currently amended) The liquid crystal display device according to Claim 5, wherein a the brightness of the liquid crystal display is improved compared to a brightness of ~~the case of~~ a liquid crystal display in which ~~constituted so that the~~ light reflected from the array substrate returns to the backlight unit after passing through a polarization layer.

7. (Currently amended) A liquid crystal display device, comprising:

Q2. *cancel.*
a liquid crystal display panel in which an array substrate and a color filter substrate are arranged to sandwich a liquid crystal layer including ~~having~~ a liquid crystal material and a reflection film is formed in an area on the array substrate corresponding to an area in the liquid crystal layer in which the liquid crystal material is oriented in a not-purposed direction when applying a voltage to the liquid crystal layer; and

a backlight unit for illuminating the liquid crystal display panel from the outside of the array substrate,

wherein a display electrode and a wiring conductively connected to the display electrode are formed on the array substrate, and

wherein the reflection film is formed on a gap between the display electrode and the wiring.

8. (Canceled).

Q3
9. (Original) The liquid crystal display device according to Claim 7, wherein a polarization layer is formed between the array substrate and the color filter substrate of the liquid crystal display panel.

10. (Currently amended) A liquid crystal display panel, comprising:

an array substrate on which a driving element for controlling a driving voltage and a display electrode to which a voltage is applied through the driving element are formed;

a liquid crystal layer filled with the liquid crystal material; and

a color filter substrate on which a color filter comprising ~~made of~~ a color-material film is formed,

the array substrate, the liquid crystal layer, and the color filter substrate being successively superposed,

wherein a metal film is formed in an area of the array substrate corresponding to an area in which an electric field including ~~having~~ a direction different from the original direction of an electric field for driving the liquid crystal material is generated,

wherein the metal film is formed on a gap between the display electrode and the driving element.

11. (Currently amended) A liquid crystal display device, comprising:

an array substrate provided with an insulating substrate, a thin film transistor formed on the insulating substrate, a polymer layer which covers the insulating substrate and in which polarization elements are dispersed, and a display electrode which is formed on the polymer layer and penetrates the polymer layer and a part of which conductively connects with the thin film transistor;

a color filter substrate disposed ~~set~~ so as to face the array substrate by keeping a predetermined gap with the array substrate; and

a liquid crystal layer located at the gap between the array substrate and the color filter substrate; and

a backlight unit for applying light to a liquid crystal display panel from the outside of the array substrate.

93
Conf.

93 cont.
12. (Original) The liquid crystal display device according to Claim 11, wherein the thin film transistor is covered with the display electrode when horizontally viewed.

94
13. (New) The liquid crystal display device according to Claim 1,
wherein the array substrate comprises:

an insulating substrate;

a thin film transistor formed on the insulating substrate;

a polymer layer covering the insulating substrate and comprising polarization elements dispersed therein; and

a display electrode formed on the polymer layer and penetrating the polymer layer, a part of the display electrode conductively connecting with the thin film transistor.

14. (New) The liquid crystal display device according to Claim 1,

wherein the array substrate comprises at least one of a common electrode, a display electrode, a gate electrode, a source electrode, and a drain electrode interposing the array substrate and the first polarization layer, and

wherein at least one of the display electrode, the gate electrode, the source electrode, and the drain electrode reflects light emitted from the backlight unit back to the backlight unit.

15. (New) The liquid crystal display device according to Claim 14,

wherein at least one of the display electrode, the gate electrode, the source electrode, and the drain electrode comprises a reflective metal film.

16. (New) The liquid crystal display device according to Claim 4,
wherein the array substrate comprises at least one of a common electrode, a display
electrode, a gate electrode, a source electrode, and a drain electrode.

17. (New) The liquid crystal display device according to Claim 16,
wherein at least one of the display electrode, the gate electrode, the source electrode, and
the drain electrode comprises a reflective metal film.

18. (New) The liquid crystal display device according to Claim 4,
wherein at least one of the display electrode, the gate electrode, the source electrode, and
the drain electrode reflects light emitted from the backlight unit, and
wherein the reflected light directly returns to the backlight unit without passing through
other layers.
